Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

Claim 1 (Currently Amended): A bicycle Bicycle trailer with a chassis formed of at least one frame part, the bicycle trailer comprising: at least one bumper which is positioned on the outside of asaid at least one frame part of the chassis and projects past the outside of thesaid at least one frame part in at least one direction.

Claim 2 (Currently Amended): The bicycle Bicycle trailer according to claim 1, wherein the said at least one bumper has a greater overall height than the said at least one frame part.

Claim 3 (Currently Amended): The bicycle Bicycle trailer according to claim 1, wherein the said at least one bumper projects past at least one edge or one of an edge and an end of the said at least one frame part.

Claim 4 (Currently Amended): The bicycle Bicycle trailer according to claim 1, wherein the said at least one bumper extends sideways past the chassis far enough to at least partially cover theone of a front orspace and a rear space between thea wheel and the chassis.

Claim 5 (Currently Amended): The bicycle Bicycle trailer according to claim 2, wherein the said at least one bumper extends sideways past the chassis far enough to at least partially cover theone of a front or space and a rear space between the wheel and the chassis.

Claim 6 (Currently Amended): <u>The bicycleBicycle</u> trailer according to claim 3, wherein <u>thesaid at least one</u> bumper extends sideways past the chassis far enough to at least partially cover <u>theone of a front orspace and a rear space between thea</u> wheel and the chassis.

Claim 7 (Currently Amended): <u>The bicycle Bicycle</u> trailer according <u>to claim 1</u>, wherein <u>the said at least one</u> bumper is hollow.

Claim 8 (Currently Amended): <u>The bicycle Bieyele</u> trailer according to claim 7, wherein the said at <u>least one</u> bumper is formed as a tube.

Claim 9 (Currently Amended): <u>The bicycle Bicycle</u> trailer according to claim 8, wherein at least one of the ends of the said at least one bumper is capped with a plug.

Claim 10 (Currently Amended): <u>The bicycle Bicycle</u> trailer according to claim 1, wherein the said at <u>least one</u> bumper takes on a weight-bearing function of the chassis.

Claim 11 (Currently Amended): <u>The bicycle Bicycle</u> trailer according to <u>claims</u>claim 1, wherein the said at least one bumper is positioned in a front area of the chassis and the said at least one bumper is formed to hold a drawbar for the bicycle trailer.

Claim 12 (Currently Amended): <u>The bicycleBicycle</u> trailer according to claim 11, wherein the drawbar is detachably connected to thesaid at least one bumper.

Claim 13 (Currently Amended): <u>The bicycle Bicycle trailer according to claim 1</u>, further comprising at least one storage area in thesaid at least one bumper.

Claim 14 (Currently Amended): The bicycle Bicycle trailer according to claim 7, further comprising at

least one storage area in thesaid at least one bumper.

Claim 15 (Currently Amended): The bicycle Bicycle trailer according to claim 1, further comprising

add-on parts located on thesaid at least one bumper.

Claim 16 (Currently Amended): The bicycle Bicycle trailer according to claim 1, wherein thesaid at

least one bumper comprises a plurality of bumpers are-positioned for protection of the front and/or

rear corners protecting one of a front corner, a rear corner, and both a front and rear corner of said at

least one frame part.

Claim 17: (Currently Amended): The bicycle Bicycle trailer according to claim 1, wherein the said at

<u>least one</u> bumper is connected to the said at least one frame part by a detachable connection.

Claim 18 (Currently Amended): The bicycle Bicycle trailer according to one of the claim 1, wherein

the said at least one bumper is positioned at about the height of a wheel hub of the bicycle trailer.

Claim 19 (New): A Bicycle trailer comprising:

a chassis having at least one frame part, and

at least one bumper positioned on the outside of said at least one frame part of the chassis,

said at least one bumper projecting past the outside of said at least one frame part in at least one

direction.

6